



## FLOORING PRODUCT INFORMATION

1. **PRODUCT NAME** ECO-GRIP® SLIP RESISTANT SAFETY FLOORING

2. **MANUFACTURING** Allied Industries International, Inc. 1088 Old Gaffney Hwy, Jonesville, SC 29353  
Phone: (864) 674-0018 Fax: (864) 674-0019

3. **PRODUCT DESCRIPTION** Eco-Grip® Slip Resistant Safety Flooring is 1/4" thick recycled PVC flooring designed for slip resistance. Eco-Grip® Slip Resistant Safety Flooring provides superior shock absorbency and is capable of withstanding high impact. The unique surface design provides excellent traction even when wet and/or greasy. Designed not to shrink or harden when exposed to animal fats or caustic chemicals.

4. **APPLICATIONS** Ideal for commercial kitchens, walk-in coolers, medical facilities, veterinary clinics, locker rooms, weight rooms, gym floors, laboratories, home workshops, entrance ways, factory and plant floors, multipurpose floors, and as a temporary gym floor cover. Eco-Grip® Slip Resistant Safety Flooring may be installed anywhere that a durable wear layer is required such as commercial kitchens, gym floors, restrooms, hallways, etc.

5. **SPECIFICATIONS** Size Sheets - 60" x 96"; Thickness: 1/4" Surface; Finish: Aggressive, textured surface for superior slip resistance. Colors: Select from manufacturer's available color selection. Eco-Grip® Slip Resistant Safety Flooring is manufactured from recycled polyvinyl chloride (PVC) with fabric strand reinforcement to increase overall product rigidity and physical strength.

6. **CLEANING INSTRUCTIONS** May be cleaned using standard commercial floor cleaning practices. For ease of maintenance, Eco-Grip® Commercial Kitchen Floor Cleaner is the recommended concentrate for commercial kitchen applications.

7. **INSTALLATION** Where to install: Eco-Grip® Slip Resistant Safety Flooring may be installed on most types of clean, dry, level and hard substrates. Eco-Grip® Safety Flooring may be used for both interior and exterior applications. Surface preparation: Surface should be clean and free of debris that may prohibit Eco-Grip® Slip Resistant Safety Flooring from laying flat. Uneven joints and cracks which create an unlevelled condition should be repaired using an approved underlayment or leveling compound. Eco-Grip® Slip Resistant Safety flooring is to be installed following normal installation procedures. Cutting and trimming can be achieved using a standard utility knife or similar razorblade-type tool.

8. **ALLIED INDUSTRIES TEST DATA** Bacteria & Mildew Resistance: Excellent ASTM G-21 Tensile ; Strength: 1600 psi Coefficient of Friction (avg): ASTM D-1894-08 Dry 1.31 Wet 1.07 Compressive Strength Elongation: 185% Fire Test: NFPA Type I Rated Hardness: instant /15 seconds 90 - 85 Average Thickness: .250 inches Weight (oz. sq. ft.): 25.16 ASTM D-751 Oxygen Index: 29.0 This list is a sampling materials ALLIED INDUSTRIES has seen in the commercial food service environment.

<http://ecotekny.com>

516.837.3294